

### **Installation Locations:**

Indoor and outdoor (provided the fan is fully undercover)

# Suitable for flat ceilings

#### **Recommended Height:**

There should be at least 2.1m between the lowest point of the fan blades and the floor.

## **Wall Controller Speed Capacitor Values:**

## Top of canopy cover to lowest point of the fan:

Approximately 310mm

## **Rotational Diameter:**

1220mm (48") / 1560mm (56") blade sweep

## Ceiling to top side of the blade:

280mm

#### Motor:

157mm x 10mm DC motor

Made with high grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and Packaging Dimensions (mm): long life.

# Weight Including Packaging:

Complete fan: 5.9kg (48") / 6.1kg (56")

# **Motor Housing:**

Materials: Polymer

Complete Fan (48"): 593L x 288W x 316H Complete Fan (56"): 656L x 288W x 316H

## **Available Motor Housing Colours:**

Matt White and Matt Black

## Accessories (Supplied separately):

Extension Down Rod 26mm diameter (includes wire

harness)

38° Ceiling Kit (for pitched ceilings)

T-Hook for ceiling roses 240V DC Wall Controller

## Blades:

Sizes: 1220mm (48") / 1560mm (56")

Materials: Polymer Blades

Available Blade Colours:

Matt White & Matt Black

Blade Pitch: 13°

## Warranty:

2 years in-home warranty on all electric components (control modules, remote control system, lighting and

accessory wall control)

3 years standard "in home" warranty

3 years extended warranty on motor only (excluding

labour)

## **Extra Information:**

Introduced into the HPI range in 2019

6 speed remote controller

Reversible

## Airflow CMH:

48" - 13,860 on High Speed (Speed 6) 56" - 14,928 on High Speed (Speed 6)

Polar 48"	Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6
RPMS	82	100	133	196	201	224
WATTS	3.5	5	7.5	18	20.6	26

Polar 56"	Speed 1	Speed 2	Speed 3	Speed 4	Speed 5	Speed 6
RPMS	78	105	123	171	183	198
WATTS	3.8	5.5	7.5	17.6	20.4	26